



Lunar Series

- Powder Coated Cast Aluminum
- ETL Listed for Wet Locations (IP65)
- Ceiling or Wall Mount
- Enclosed and Gasketed
- BAA Compliant
- Optional Microwave Sensor (Occupancy/Photocell)
- Mounting Hardware Included

Specifications Subject to Change without Notice



Ordering Information

Example LRO-L-22W-U-30K-B-WP-MS

Item Series

M2010	LRO	A	Lunar Round Wall/Ceiling Open Frame
M2020	LRE	B	Lunar Round Wall Eyelid

Light Source

L-14W 14 Watt LED 120V **-30K** 3000K, 80 CRI, 1430 Lumens **-40K** 4000K, 80 CRI, 1500 Lumens

L-32W 32 Watt LED 120V **-30K** 3000K, 80 CRI, 2700 Lumens **-40K** 4000K, 80 CRI, 2750 Lumens

L-22W-U 22 Watt LED 120-277V **-30K** 3000K, 70 CRI, 1704 Lumens **-40K** 4000K, 70 CRI, 1824 Lumens

Body

B Black **W** White

Lens

WP White Polycarbonate

Options

EM Emergency LED Array Board, Charger & Battery, Minimum 90 Minute, 4 Watt, Fixture Integrated, Test Button and Indicator Light

MS Microwave Sensor, Occupancy and Photo Control, Dip Switch Adjustable