



Protek Series

- Fade & Rust Resistant Composite Construction
- UL Listed for Wet Locations
- Ceiling or Wall Mount
- BAA Compliant
- Optional Microwave Sensor (Occupancy/Photocell)
- Knockouts for Conduit Installation
- Mounting Hardware Included

Specifications Subject to Change without Notice



Ordering Information

Example PR-L-22W-U-B-WP-MS

Item	Series	
M2060	PR	A Protek Round Wall/Ceiling
M2070	PS	B Protek Square Wall/Ceiling
Light Source		
L-14W 14 Watt LED 120V -30K 3000K, 80 CRI, 1430 Lumens -40K 4000K, 80 CRI, 1500 Lumens		
L-22W-U 22 Watt LED 120-277V -30K 3000K, 70 CRI, 1704 Lumens -40K 4000K, 70 CRI, 1824 Lumens		
MB Medium Base, Incandescent, Sockets Only, 2 X 40W Max		
MBL Medium Base with 2 LED Lamps -30K 3000K, 90 CRI LED Lamps -40K 4000K, 80 CRI LED Lamps		
Body/Lens		
Body	W White B Black	Lens WP White Polycarbonate
Options		
EM Emergency LED Array Board, Charger & Battery, Minimum 90 Minute, 4 Watt, Fixture Integrated, Test Button and Indicator Light		
MS Microwave Sensor, Occupancy and Photo Control, Dip Switch Adjustable		